

AD-2045 WET HORIZONTAL UNIT



GENERAL DESCRIPTION

The Magnaflux® AD-2045 is one of our most economical standard wet bench units. It offers great particle mobility for finding surface and sub-surface defects, and the versatility of using AC or FWDC magnetization. The two outputs are independently adjustable to set each magnetic field, circular or longitudinal.

BENEFITS

- Versatility of using AC (surface defects) or FWDC (sub-surface defects)
- Shot time can be adjusted to meet different inspection requirements or needs
- Footswitch to free-up hands for inspection

EXTERIOR

- Innovative pump system for fluid delivery, agitation with easy maintenance access
- Push bar design for easy activation
- Current assurance indicator for magnetic current flow
- Large, easy to read Digital Ammeter
- Independent Contact and Coil Current Controls
- 12 inch (30 cm) diameter coil
- Footswitch-activated pneumatic headstock
- Adjustable tailstock with crank
- Stainless steel tank
- Front and rear maple hardwood grilles

INTERIOR

- Microprocessor control advanced technology; reduce components and increase reliability
- Solid state circuitry
- Liquid Resistant panels, allow ventilation while inhibiting fluid intrusion

SPECIFICATIONS

- 4000 amp AC/5000 amp FWDC magnetizing current capability at contacts
- One Touch Decaying AC Demagnetization
- Duty Cycle 0.5 seconds on, 10 Seconds off (5% with Maximum of 5 seconds)
- 54 inch (137 cm) headstock/tailstock capacity
- Infinitely variable current control
- Available Voltages: 230, 380, 415, 460, 575, 50 or 60 hertz, single phase power
- Recommended 20 Gallon (75 Liter) Tank Fluid Capacity
- Minimum 80 PSI with 5 SCFM capability
- 89" (224 cm) x 41" (104 cm) Foot Print, allow 24" (61 cm) per side for ventilation

OPTIONAL FEATURES

- 16" coil (41 cm) w/raising block up-grade (In lieu of 12" coil)
- 20" coil (51 cm) w/raising block up-grade (In lieu of 12" coil)
- 19.5" inch (50 cm) clam-shell coil (3-turn) w/raising block up-grade (In lieu of 12" coil)
- Reinforced Rail for Heavier Part Load - 4,000 lbs. (1815kg) part capacity
- Oversized Contact Assembly (12"x 12") for headstock & tailstock
- Rotating Contacts (70 lb. part capacity) (Minimum 16" coil required)
- NRTL Certification to CSA C22.2 No. 61010-1
- Dual Palm Button
- Configure Unit for 102" Part
 - Recommended 32 Gallon (122 Liter) Tank Fluid Capacity
 - 136" (346 cm) x 41" (104 cm) Foot Print, allow 24" (61 cm) per side for ventilation
- Configure Unit for 146" Part
 - Recommended 55 Gallon (209 Liter) Tank Fluid Capacity
 - 80" (458 cm) x 41" (104 cm) Foot Print, allow 24" (61 cm) per side for ventilation

MATERIALS START UP KIT

Please Choose Water Bath or Oil Bath Start-Up Kit

- Centrifuge Tube, 100 ml, 0-1.0 ml in 0.05 ml increments (Part Number 8493)
- Centrifuge Tube Aluminum Stand (Part Number 1837A)
- Field Indicator (Part Number 2480)
- Two Double-Braided Copper Pads with V- Blocks (Part Number 18948)
- Pie Field Indicator (Part Number 169799)
- UV Filtering Safety Glasses - non tinted (Part Number 506249)

For Oil Baths (Part Number 621452)

- Carrier II oil vehicle, 55 gallon drum
- 14A wet method magnetic particles, 1 lb. bottle

For Water Baths (Part Number 621453)

- 14A Redi-Bath, 6 - 27 oz. bottles for Water Baths

UNIT COMPARISON CHART**AD-2045**

4,000 amps AC or 5,000 amps FWDC - 54" (137 cm)
2 Outputs - Contacts, 12" ID Coil
Voltages Available (230V or Higher)
Standard Coil May be Substituted for 16" or 20" ID Coil

ADH-2045

4,000 amps AC or 5,000 amps HWDC - 54" (137 cm)
2 Outputs - Contacts, 12" ID Coil
Voltages Available (230V or Higher)
Standard Coil May be Substituted for 16" or 20" ID Coil

A-2030

3,000 amp AC - 54" (137 cm)
2 Outputs - Contacts, 12" ID Coil
Voltages Available (230V or Higher)
Standard Coil May be Substituted for 16" or 20" ID Coil

SIZE COMPARISON CHART

UNIT SIZE	PART LENGTH CAPACITY	DIMENSIONS	TANK CAPACITY
Standard	54 Inches (137 cm)	89" x 41" x 61"	20 Gal (75L)
Long	102 Inches (259 cm)	136" x 41" x 61"	32 Gal (122L)
Extra Long	146 Inches (371 cm)	180" x 41" x 61"	55 Gal (209L)