



A-SERIES					
Series	Magnetizing Current Capacity			Maximum Clamping Length*	Coil Inside Diameter*
	AC (amp)	DC (amp FWDC)	HWDC (amp)		
A-2030	3,000			54 in / 137 cm (102 in / 259 cm, 146 in / 370 cm)	12 in / 30 cm (16 in / 40 cm)
AD-2045	4,000	5,000			
ADH-2045	4,000		5,000		

Series	Particle-Bath Tank Capacity*	Available Voltages	Available Frequencies
A-2030	20 gal / 75 L (32 gal / 121 L, 55 gal / 208 L)	230, 380, 415, 460, 575 V	50 or 60 hertz
AD-2045			
ADH-2045			

* Optional features shown in italics



MD-SERIES					
Series	Magnetizing Current Capacity			Maximum Clamping Length*	Coil Inside Diameter*
	AC (amp)	DC (amp FWDC)	DC (amp HWDC)		
MD-2030	2,500	3,000	3,000	41 in / 104 cm	-
MD-2060	5,000	6,000	6,000	41 in / 104 cm (89 in / 226 cm)	-
MD3-2060	5,000	6,000	6,000	41 in / 104 cm (89 in / 226 cm, 133 in / 337 cm)	16 in / 40 cm (20 in / 50 cm)
Series	Particle-Bath Tank Capacity*		Available Voltages		Available Frequencies
MD-2030	20 gal / 75 L (32 gal / 121 L) 55 gal / 208 L		230, 380, 415, 460, 575 V		50 or 60 hertz
MD-2060					
MD3-2060					

* Optional features shown in italics



D-SERIES			
Series	Magnetizing Current Capacity	Maximum Clamping Length*	Coil Inside Diameter*
D-2060	6,000 amp 3-Phase FWDC	54 in / 137 cm (102 in / 259 cm, 146 in / 370 cm)	12 in / 30 cm (16 in / 40 cm, 20 in / 50 cm, 25 in / 63 cm, 30 in / 76 cm, 36 in / 91 cm)
D-2100	10,000 amp 3-Phase FWDC	54 in / 137 cm (102 in / 259 cm, 146 in / 370 cm)	16 in / 40 cm (20 in / 50 cm, 25 in / 63 cm, 30 in / 76 cm, 36 in / 91 cm)
Series	Particle-Bath Tank Capacity*	Available Voltages	Available Frequencies
D-2060	20 gal / 75 L (32 gal / 121 L, 55 gal / 208 L)	230, 380, 415, 460, 575 V	50 or 60 hertz
D-2100			

* Optional features shown in italics